

Planar DC/DC Transformer

ER/ER(Plate) 22

Core Size (LxHxW) :27.5x13x23 Unit : mm




Power Capacity 50 to 150 W

Frequency Range :100K~300KHz


Features

- This planar x'fmr is suitable for forward DC/DC converter with resonance reset.

Mechanical Dimension :
Unit : mm



2. SCHEMATIC :



Electrical Characteristics:

TRANSFORMER								
PART NO.	INDUCTANCE		OPERATING FREQUENCY	TURN RATIO (1-3) : (4-6) : (10-12) : (7-9)	DIELECTRIC STRENGTH		AMBIENT TEMPERATURE	WEIGHT
	L (1-3)	L (4-6)			PRI TO SEC	SEC TO CORE		
PLT2215-001	9.0uH Min.	144.0uH Min.	250KHz	2 : 8 : 2 : 2	2000Vdc	2000Vdc	+10°C to +70°C	13.5gr

EQ/EQ(Plate) 25

Core Size (LxHxW) :30.5x13x26 Unit : mm





Power Capacity 50 to 360 W

Frequency Range :100K~500KHz

Features

- This planar x'fmr is suitable for forward converter's transformer and for use on Linear Technology's LT1950.

Mechanical Dimension:
Unit : mm



Electrical Characteristics:

TRANSFORMER						
PART NO.	INDUCTANCE	OPERATING FREQUENCY	TURN RATIO (2-3) : (1-4) : (7-8) : (5-6)	DIELECTRIC STRENGTH PRI TO SEC	AMBIENT TEMPERATURE	WEIGHT
	L(2-3)					
PLT2518-001	97.0uH Min	350KHz	5 : 2 : 6 : 6	2250Vdc	+10°C to +70°C	23.5gr



DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 252, SAN YING ROAD, KUEISAN INDUSTRIAL ZONE, TAOYUAN SHIEN, 333, TAIWAN, R.O.C.

TEL: 886-3-3591968; FAX: 886-3-3591991

http://www.deltawww.com